


## Airgun umbilicals

With a choice of Aramid-reinforced and collapse-resistant hoses, Fibron's airgun umbilicals are designed and manufactured to the highest standards. Our selection of materials, and carefully researched component lay-angles deliver improved performance in even the most challenging environments.


SU0044	
Finished diameter	73.0mm
Weight in air	6,000kg/km
Weight in seawater	1,800kg/km
Minimum dynamic bend radius	700mm
Minimum breaking load	250kN



**Contents**

- 1 x 1" 207 bar hose
- 70 x 0.75mm<sup>2</sup> conductors
- 48 x 1.5mm<sup>2</sup> conductors
- 3 x 4 MM FIST units

SU0047	
Finished diameter	57.0mm
Weight in air	2,900kg/km
Weight in seawater	130kg/km
Minimum dynamic bend radius	700mm
Minimum breaking load	50kN




**Contents**

- 1 x 3/4" 207 bar hose
- 40 x 0.75mm<sup>2</sup> conductors
- 24 x 1.5mm<sup>2</sup> conductors

## Other seismic umbilicals

All of our seismic cables are designed and manufactured to our customers' precise requirements. Rest assured that whatever your requirements, our experienced team will do all they can to help.

SU0051	
Finished diameter	51.5mm
Weight in air	3,850kg/km
Weight in seawater	1,700kg/km
Minimum dynamic bend radius	800mm
Minimum breaking load	360kN



**Contents**

- 1 x 1/2" 207 bar hose
- 20 x 0.75mm<sup>2</sup> conductors
- 10 x 1.5mm<sup>2</sup> conductors
- 6 x 6mm<sup>2</sup> conductors
- 1 x 4 MM FIST unit